



# CLAYMAN

Morells Barn • Park Lane • Lower Bognor Road • Lagness • Chichester • West Sussex • PO20 1LR  
Telephone: +44 (0) 1243 265845 (2 lines + ansaphone) • Facsimile: +44 (0) 1243 267582

Email: [Info@claymansupplies.co.uk](mailto:Info@claymansupplies.co.uk) • [www.claymansupplies.co.uk](http://www.claymansupplies.co.uk)

## SAFETY DATA SHEET

1222	SOFT GREEN DECORATING SLIP
------	----------------------------

1. Identification of substance/preparation and of the company undertaking	
Trade Name:	Soft Green Decorating Slip
Chemical Name:	Mixture of chemicals
Synonyms:	None

2. Composition /information on ingredients			
Component	CAS	EINECS	% of composition
Cobalt oxide CO <sub>3</sub> O <sub>4</sub>	1306-06-1	2151572	3

3. Hazards Identification	
Inhalation	Excessive exposure may cause symptoms of chronic lung disease.
Ingestion	The product is of low solubility in body fluids and it is likely to be of low toxicity
Eyes	May cause physical irritation and inflammation.
Skin	The material is not a primary irritant but as with any abrasive powder it may give rise to minor irritation. Some cobalt compounds have been shown to cause dermatitis and sensitisation, but this is unlikely with our product.

4. First Aid Measures	
Inhalation	Remove patient to fresh air, loosen tight clothing and seek medical attention.
Ingestion	Do not induce vomiting, seek medical advice.
Eyes	Wash immediately with copious amounts of water.
Skin	Wash affected areas with water.

5. Fire Fighting Hazards	
Extinguishing media	Suitable for surrounding fire conditions.
Special Exposure hazard	In the event of fire the product may emit harmful or toxic fumes
Personal protective equipment	Self-contained breathing apparatus.

6. Accidental Release Measure	
Leaks and Spills	Use suitable vacuum equipment where reasonably practicable, otherwise damp down and scoop into a receptacle.
Personal protective equipment	Respiratory protective equipment.



7. Handling & Storage	
Handling	Do not eat, drink, or smoke in areas where the material is used. Wash thoroughly after handling the material.
Storage	Store in a dry area.

8. Exposure Control/Personal Protection	
Engineering controls	Adequate ventilation should be provided so that Occupational Exposure Limits are not exceeded. Local Exhaust Ventilation is normally recommended.
Personal protective equipment	Where LEV is not practicable and exposure is likely to be excessive, approved respiratory protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves and overalls are recommended for prolonged contact.

9. Physical & Chemical Properties	
Appearance and Odour	Liquid, odourless
Flash point (°C)	Not applicable
Flammability	Not applicable
Explosive properties	Non explosive
Oxidising properties	None
Specific Gravity	3-5
pH value	7 (insoluble in water)
Melting point (°C)	Not available

10. Stability & Reactivity	
Chemical stability	The material is stable
Conditions/ materials to avoid	None known
Hazardous decomposition products	None known
Hazardous polymerization products	None

11. Toxicological Information			
Acute toxicology	LD50	Oral	>2000 mg/kg
	LD50	Dermal	Not known
	LD50	Inhalation	Not known
Health effects	Prolonged or repeated exposure above Occupational Exposure Standards may cause fibrosis of the lungs.		

12. Ecological Information	
Ecotoxicity	Not known
Persistence	Not known



<b>13. Disposal Considerations</b>
Dispose in accordance with current waste Disposal regulations (for UK – Control of Pollution {Special Waste} Regulations 1980). Landfill is the most appropriate method.

<b>14. Transport Information</b>		
UN/SI No	Not classified	
UN Class	Not classified	
Packing group	Not classified	
Road	UK	Not classified
	ADR	Not classified
Sea	IMO	Not classified
Air	ICAO	Not classified

<b>15. Regulatory Information</b>			
EC Supply labelling	Harmful X <sub>n</sub>		
R phrases	R20	Harmful by inhalation	
S phrases	S13	Keep away from food, drink and animal feeding stuffs	
	S22	Do not breathe dust.	
UK Occupational exposures limits (Refer to HSE Guidance note EH40)	Mg/m <sup>3</sup>	8 hr TWA	% in product
Cobalt compounds (as Co)	0.10		3
Crystalline silica	0.40		
In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitutes the user's assessment of workplace risk.			

<b>16. Other Information</b>	
References	
COSHH ACOP	HSC approved Code of Practice for the Control of Substances Hazardous to Health Regulations 1994.
CHIP 96	Chemicals (Hazard Information and Packaging for Supply) Regulations 1996
CHIP SDS ACOPS	HSC Approved Code of Practice for Safety data sheets in accordance with regulation 6 of the CHIP regulations.
HSE EH40	HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with COSHH regulations.