



# CLAYMAN

Morells Barn • Park Lane • Lower Bognor Road • Lagness • Chichester • West Sussex • PO20 1LR  
Telephone: +44 (0) 1243 265845 (2 lines + ansaphone) • Facsimile: +44 (0) 1243 267582

Email: [info@claymansupplies.co.uk](mailto:info@claymansupplies.co.uk) • [www.claymansupplies.co.uk](http://www.claymansupplies.co.uk)

## SAFETY DATA SHEET

### CRYSTALITE BRUSH-ON GLAZES

PRODUCT NAME: CRYSTALITE GLAZES –  
CR069 – COBALT BLACK

ISSUED: March 2007

#### Lead Free and Cadmium Free Glazes

CONTACT NUMBER: 01243 265845

#### HAZARDOUS INGREDIENTS

ENTITY	%	CAS NO	ACGIH TLV	OSHA PEL
ZIRCONIUM SILICATE	0 – 9%	10101-52-7	5 mg / m <sup>3</sup> (as Zr)	5 mg / m <sup>3</sup> (as Zr)
CLAY/POTASH	< 15%	1302-78-9	N/A	N/A
CALCINED ALUMINA	0 - 2%	1344-28-1	10 mg / m <sup>3</sup>	5 mg / m <sup>3</sup>
SILICA	0 - 6%	14808-60-7 0.	1 mg / m <sup>3</sup>	0.1 mg / m <sup>3</sup>
ZINC OXIDE	0 - 6%	1314-13-2	2 mg / m <sup>3</sup>	5 mg / m <sup>3</sup>

#### PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Colour dependent on pigments present
ODOUR:	Negligible
BOILING POINT:	N/A
MELTING POINT:	> 400°C
VAPOUR PRESSURE:	N/A
SPECIFIC GRAVITY:	1.2 – 1.45 @ 25°C
FLASH POINT:	N/A
FLAMMABILITY LIMITS:	No data
SOLUBILITY IN WATER:	Negligible
VISCOSITY:	No data
pH:	7.0 – 8.5
VOLATILE ORGANIC COMP:	7 – 14%



## HAZARDS IDENTIFICATION

### SILICA

Crystalline Silica may be present. Crystalline silica may cause irritation to eyes, skin and the respiratory tract. Prolonged or repeated inhalation of silica, in excess of TLV, may lead to delayed lung injury (silicosis). This material is listed as a possible carcinogen.

Routes of Entry: Ingestion. Absorption through skin negligible. Inhalation only if sprayed.

## FIRST AID MEASURES

**SWALLOWED:** Dilute by drinking water.

**EYE:** Flush eyes with copious quantities of water for at least 15 minutes. If irritation persists contact a physician.

**SKIN:** Wash skin with soap and water.

**INHALED:** Remove from exposure. Apply artificial respiration if breathing has stopped and contact physician.

## FIRE/EXPLOSION HAZARD

**FLASH POINT:** N/A

**FLAMMABLE LIMITS:** N/A

**EXTINGUISHING MEDIA:** Not combustible

**SPECIAL FIRE FIGHTING PROCEDURE:** None

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None

## ACCIDENTAL RELEASE MEASURES

**Spillage:** Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum or wash into a receptacle for disposal.

**Waste Disposal:** Follow Federal or State and Local regulations for disposal. Testing of the waste may be required to determine status under hazardous waste regulations.

## HANDLING AND STORAGE

**ENGINEERING CONTROL:** None

**WORK PRACTICES:** Store away from food. Do not smoke, eat or drink while handling.

**PROCEDURE/EQUIPMENT:** None.

## EXPOSURE CONTROLS/PERSONAL PROTECTION

Use of the following protective measures are strongly recommended if the glazes are to be applied by spraying.

The work hygiene practices apply regardless of the method of application.

**RESPIRATORY PROTECTION:** Use NIOSH approved dust and/or fume respirator as necessary.

**VENTILATION:** Local Exhaust for spraying.



**PROTECTIVE GLOVES:** N/A  
**EYE PROTECTION:** For spraying.  
**OTHER PROTECTION:** Wear appropriate clean, protective clothing such as, but not limited to overalls, smocks and aprons.  
**WORK PRACTICES:** Food, beverages and smoking materials should not be in the work area. Hygiene is very important. Wash thoroughly before eating, drinking and smoking or applying cosmetics.

#### STABILITY AND REACTIVITY DATA

**INCOMPATIBILITY:** N/A  
**STABILITY:** Stable.  
**HAZARDOUS DECOMPOSITION:** N/A  
**HAZARDOUS POLYMERISATION:** N/A  
**CONDITIONS TO AVOID:** Fumes from firing, inhalation of spray.

#### TOXICOLOGY INFORMATION

##### USA

**Hazard to Humans:** None during normal use. Harmful if inhaled or swallowed.

##### DO NOT SPRAY APPLY

If glaze is spray applied the following warnings apply: Warning: Contains Quartz.

1. Possible cancer agent based on tests with laboratory animals.
2. Exposure may cause lung damage.
3. Keep out of reach of children; avoid inhalation.

This product contains chemicals known to the State of California to cause cancer.

**Health Hazards (acute and chronic):** Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs.  
**Additional information:** Frits are fused silica glass like substances. The bioavailability may be limited because of the physical nature of the frit.

#### ECOLOGICAL INFORMATION

**MOBILITY:** N/A  
**PERSISTENCE/DEGRADABILITY:** N/A  
**BIOACCUMULATION:** N/A  
**ECOTOXICITY:** N/A

#### DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHOD:** Follow Federal, State or Local regulations for disposal. Testing of waste may be required to determine status under hazardous waste regulations.  
**WASTE RESIDUE/UNUSED PRODUCT:** Can be land filled according to local regulations.  
**CONTAMINATED PACKAGING:** Can be land filled according to local regulations.



**TRANSPORTATION  
UN NUMBER:**

N/A

**REGULATORY INFORMATION**

Silica is listed by California, Proposition 65  
Silica is listed on the IARC, OSHA or NTP carcinogen list.  
All ingredients are on U.S. TSCA/EC/AICS/DSL Inventory.  
See local requirements.

**EU Status:** -

**Symbol:** -

**EEC**

R-20/22 Harmful by inhalation and if swallowed  
R-37/38 Irritating to respiratory system and skin  
S-20/21 When using do not eat, drink or smoke  
S-22 Do not breathe dust or spray  
S-24/25 Avoid contact with skin and eyes  
S-36/37 Wear suitable protective clothing and gloves  
S-45 In case of accident or if you feel unwell, seek medical advice immediately

**WHMIS Status:** Not controlled

**ADDITIONAL INFORMATION:**

This information is provided without warranty, representation, inducement or license of any kind, except that it is accurate to the best of knowledge of Clayman or obtained from sources believed to be accurate. Clayman does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct their own tests before using any product. Read the product label.

**END OF MATERIAL SAFETY DATA SHEET**