



CLAYMAN

Morells Barn • Park Lane • Lower Bognor Road • Lagness • Chichester • West Sussex • PO20 1LR
Telephone: +44 (0) 1243 265845 (2 lines + ansaphone) • Facsimile: +44 (0) 1243 267582

Email: Info@claymansupplies.co.uk • www.claymansupplies.co.uk

SAFETY DATA SHEET

2207	SPRING CLEAR GLAZE
------	--------------------

1. Identification of substance/preparation and of the company undertaking

Trade Name:	Spring Clear Glaze
Chemical Name:	-

2. Composition /information on ingredients

When supplied dry, this material offers the normal hazards associated with any dry powder of a slightly abrasive nature. In dry state, forms low toxicity dust with an occupational exposure value of 10 Mg/m³ (nuisance dust). In slop state, organic binders / antibacterial agents may be present – concentration less than 0.3% by weight.

3. Hazards Identification

Non-hazardous.

4. First Aid Measures

Eye Contact:	Flood with clean water for 15 minutes and seek medical advice if irritation persists.
Skin Contact:	Remove contaminated clothing. Wash the affected areas with soap and water. If irritation persists seek medical advice.
Ingestion:	Do not induce vomiting. If patient is conscious give water to drink.
Inhalation:	Seek immediately a source of fresh air. If respiratory tracts are irritated, seek medical advice.

5. Fire Fighting Hazards

The product is not explosive or combustible. Standard fire fighting techniques only are required i.e. water, sand, carbon dioxide, chemical foam extinguishers etc.

6. Accidental Release Measure

Large spillages of slop material should be absorbed with an inert material e.g. sand. Remove any dry material either by a vacuum cleaner fitted with an efficient filter, or by wet sweeping to avoid creating dust. Any collected waste must be stored in a suitable container prior to disposal.



7. Handling & Storage	
Prevent extensive contact with eyes, skin and clothing. Wash hands / skin after use. Do not eat, drink or smoke when using this material and keep away from animal feeding stuffs.	
Local exhaust ventilation is recommended to comply with occupational exposure limits (see Guidance Note EH40 – latest edition).	
Store in secure containers in dry conditions, avoiding extremes of temperature and protect from frost.	

8. Exposure Control/Personal Protection	
In conditions of spray mist or product dust, local exhaust ventilation should be provided to comply with occupational exposure limits (see Guidance Note EH40 – latest edition).	
Hand / Skin Protection:	Gloves (plastic or rubber, cotton lined).
Eye Protection:	Goggles (BS2092, Grade 1 : CDM).
Respiratory Protection:	If local exhaust ventilation is not adequate, HSE approved respiratory equipment must be provided.

9. Physical & Chemical Properties	
Form:	Fine dry powder.
Odour:	Odourless.
Melting Point:	Not applicable.
Solubility:	Not applicable.
Flash Point:	Not applicable.
Oxidising Properties:	Not applicable

10. Stability & Reactivity
Stable over normal conditions.

11. Toxicological Information
No specific data available.

12. Ecological Information
No specific data available.

13. Disposal Considerations
Material should be disposed of to comply with local regulations.

14. Transport Information
None hazardous for transportation – no special precautions required.



15. Regulatory Information
None hazardous.
16. Other Information
Good industrial hygiene practices are recommended when handling and using this product.