



CLAYMAN

Morells Bam • Park Lane • Lower Bognor Road • Lagness • Chichester • West Sussex • PO20 1LR
Telephone: +44 (0) 1243 265845 (2 lines + ansaphone) • Facsimile: +44 (0) 1243 267582

Email: Info@claymansupplies.co.uk • www.claymansupplies.co.uk

SAFETY DATA SHEET

5562	COBALT OXIDE
------	--------------

1. Identification of substance/preparation and of the company undertaking	
Trade Name:	Cobalt Oxide
Chemical Name:	Cobalt Oxide
Synonyms:	Cobalto-cobaltic oxide, but the product is really a mixture.

2. Composition /information on ingredients			
Component	CAS	EINECS	% of composition
Cobalt oxide Co_3O_4	1308-06-1	2151572	>95%
Cobalt oxide CoO	1307-96-6	2151546	<5%
Nickel Oxide NiO	113-99-1	2152157	<0.9%

3. Hazards Identification	
Inhalation	Excessive exposure may cause symptoms of chronic lung disease
Ingestion	The product is of low solubility in body fluids and it is likely to be of low toxicity.
Eyes	May cause physical irritation and inflammation.
Skin	Some cobalt compounds have been shown to cause dermatitis and sensitisation.

4. First Aid Measures	
Inhalation	Remove patient to fresh air, loosen tight clothing and seek medical attention.
Ingestion	Do not induce vomiting, seek medical attention.
Eyes	Wash immediately with copious amounts of water.
Skin	Wash affected area with water.

5. Fire Fighting Hazards	
Extinguishing media	Suitable for surrounding fire conditions.
Special Exposure hazard	In the event of a fire the product may emit harmful or toxic fumes.
Personal protective equipment	Self contained breathing apparatus.



6. Accidental Release Measure	
Leaks and Spills	Use suitable vacuum equipment where reasonably practicable, otherwise damp down and scoop into a receptacle.
Personal protective equipment	Respiratory protective equipment.

7. Handling & Storage	
Handling	Do not eat, drink or smoke in areas where the material is used. Wash thoroughly after handling the material.
Storage	Store in a dry area.

8. Exposure Control/Personal Protection	
Engineering controls	Adequate ventilation should be provided so that Occupational Exposure Limits are not exceeded. Local Exhaust Ventilation is normally recommended.
Personal protective equipment	Where LEV is not practicable and exposure is likely to be excessive, approved respiratory protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves and overalls are recommended for prolonged contact.

9. Physical & Chemical Properties	
Appearance and Odour	Black powder, odourless
Flash Point (°C)	Not applicable
Flammability	Not applicable
Explosive Properties	Non-explosive
Oxidising properties	None
Specific gravity	3-5
pH value	7 (insoluble in water)
Melting point (°C)	Not available

10. Stability & Reactivity	
Chemical stability	The material is stable
Conditions/ materials to avoid	Soluble in acids
Hazardous decomposition products	None known
Hazardous polymerization products	None

11. Toxicological Information			
Acute toxicology	LD50	Oral	>2000mg/kg
	LD50	Dermal	Not known
	LD 50	Inhalation	Not known
Health effects	Prolonged or repeated exposure above Occupational Exposure Standards may cause aggravation of asthma, sensitisation, cancer, blood disorders and damage to the heart, thyroid and pancreas.		



12. Ecological Information	
Ecotoxicity	Not known
Persistence	Not known

13. Disposal Considerations	
Dispose in accordance with current waste Disposal regulations (for UK – Control of Pollution {Special Waste} Regulations 1980). Landfill is the most appropriate method.	

14. Transport Information		
UN/SI No.	Not classified	
UN Class	Not classified	
Packing group	Not classified	
Road	UK	Not classified
	ADR	Not classified
Sea	IMO	Not classified
Air	ICAO	Not classified

15. Regulatory Information			
EC Supply Labelling	Toxic		
R phrases	R20/22	Harmful by inhalation and if swallowed.	
	R43	May cause sensitisation by skin contact.	
	R49	May cause cancer by inhalation.	
S phrases	S24	Avoid contact with skin.	
	S36/37	Wear suitable protective clothing and gloves.	
	S45	In case of accident or if you feel unwell, seek medical advice immediately.	
	S53	Avoid exposure – obtain special instructions before use.	
UK Occupational exposures limits (Refer to HSE Guidance note EH40)	Mg/m ³	8 hr TWA	% in product
Cobalt compounds (as Co)		0.10	70%
In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitute the user's assessment of workplace risk.			



16. Other Information	
References	
COSHH ACOP	HSC approved Code of Practice for the Control of Substances Hazardous o Health Regulations 1994
CHIP 96	Chemicals (Hazardous Information and Packaging for Supply) Regulations 1996
CHIP SDS ACOPS	HSC Approved Code of Practice for Safety data Sheets in accordance with Regulation 6 of the CHIP regulations.
HSE EH40	HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with the COSHH regulations.