



CLAYMAN

Morells Barn • Park Lane • Lower Bognor Road • Lagness • Chichester • West Sussex • PO20 1LR
Telephone: +44 (0) 1243 265845 (2 lines + ansaphone) • Facsimile: +44 (0) 1243 267582

Email: Info@claymansupplies.co.uk • www.claymansupplies.co.uk

SAFETY DATA SHEET

5564	COPPER OXIDE
------	--------------

1. Identification of substance/preparation and of the company undertaking	
Trade Name:	Copper Oxide
Chemical Name:	Cupric Oxide
Synonyms:	Copper (II) Oxide

2. Composition /information on ingredients			
Component	CAS	EINECS	% of composition
Copper (II) Oxide	1313-38-0`	2152691	>98

3. Hazards Identification	
Inhalation	Excessive exposure may cause symptoms of chronic lung disease.
Ingestion	Ingestion of large amounts may cause vomiting, diarrhoea, nausea, salivation and intense pain.
Eyes	May cause physical irritation and inflammation.
Skin	The material is not a primary irritant, but as with any abrasive powder it may give rise to minor irritation. Discolouration of the skin may occur, without indicating injury. Some people may become allergic to copper and develop dermatitis and long lasting sensitivity.

4. First Aid Measures	
Inhalation	Remove patient to fresh air, loosen tight clothing and seek medical attention
Ingestion	Do not induce vomiting, seek medical advice.
Eyes	Wash immediately with copious amounts of water.
Skin	Wash affected areas with water.

5. Fire Fighting Hazards	
Extinguishing Media	Suitable for surrounding fire conditions
Special Exposure Hazard	In the event of a fire the product may emit harmful or toxic fumes
Personal protective equipment	None other than required for surrounding fire conditions



6. Accidental Release Measure	
Leaks and Spills	Use suitable vacuum equipment where reasonably practicable, otherwise damp down and scoop into a receptacle.
Personal protective equipment	Respiratory protective equipment.

7. Handling & Storage	
Handling	Do not eat, drink or smoke in areas where the material is used. Wash thoroughly after handling the material.
Storage	Store in a dry area.

8. Exposure Control/Personal Protection	
Engineering controls	Adequate ventilation should be provided so that Occupational Exposure Limits are not exceeded. Local exhaust Ventilation is normally recommended.
Personal Protective Equipment	Where LEV is not practicable and exposure is likely to be excessive, approved respiratory protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves and overalls are recommended for prolonged contact.

9. Physical & Chemical Properties	
Appearance and Odour	Black powder, odourless
Flash point (°C)	Not applicable
Flammability	Not applicable
Explosive properties	Non-explosive
Oxidising properties	None
Specific Gravity	About 6
pH Value	7 (Insoluble in water)
Melting point (°C)	1350°C but starts to decompose from 1100°C

10. Stability & Reactivity	
Chemical Stability	The material is stable
Conditions/ materials to avoid	Powdered or reactive metals, hydrogen sulphide, phthalic onhydride, dichloromethylsilane, reductants.
Hazardous decomposition products	None known
Hazardous polymerization products	None

11. Toxicological Information			
Acute toxicology	LD50	Oral	470mg/kg
	LD50	Dermal	Not known
	LD50	Inhalation	Not known
Health Effects	Prolonged or repeated exposure above Occupational Exposure Standards may cause fibrosis of the lungs.		



12. Ecological Information	
Ecotoxicity	Not known but it is used as a fungicide.
Persistence	Not known

13. Disposal Considerations	
Dispose in accordance with current waste Disposal regulations (for UK – Control of Pollution {Special Waste} Regulations 1980). Landfill is the most appropriate method.	

14. Transport Information		
UN/SI No.	Not restricted	
UN Class	Not restricted	
Packing group	Not restricted	
Road	UK	Not restricted
	ADR	Not restricted
Sea	IMO	Not restricted
Air	ICAO	Not restricted

15. Regulatory Information			
EC Supply Labelling	Harmful		
R Phrases	R20/22	Harmful by inhalation and if swallowed.	
	R33	Danger of cumulative effect.	
S phrases	S13	Keep away from food, drink and animal feeding stuff	
	S20/21	When using do not eat, drink or smoke.	
UK Occupational exposures limits (Refer to HSE Guidance note EH40)	Mg/m ³	8 hr TWA	% in product
Dusts – Total Inhalable		10	-
Dusts – Total respirable		5	-
In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitute the user's assessment of workplace risk.			



16. Other Information	
References	
COSHH ACOP	HSC approved Code of Practice for the Control of Substances Hazardous to Health Regulations 1994
CHIP 96	Chemicals (Hazardous Information and Packaging for Supply) Regulations 1996
CHIP SDS ACOPS	HSC Approved Code of Practice for Safety data Sheets in accordance with Regulation 6 of the CHIP regulations.
HSE EH40	HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with the COSHH regulations.