



# CLAYMAN

Morells Barn • Park Lane • Lower Bognor Road • Lagness • Chichester • West Sussex • PO20 1LR  
Telephone: +44 (0) 1243 265845 (2 lines + ansaphone) • Facsimile: +44 (0) 1243 267582

Email: [Info@claymansupplies.co.uk](mailto:Info@claymansupplies.co.uk) • [www.claymansupplies.co.uk](http://www.claymansupplies.co.uk)

## SAFETY DATA SHEET

5176	WHITING
------	---------

<b>1. Identification of substance/preparation and of the company undertaking</b>	
Trade Name	Whiting
Chemical Name	Calcium Carbonate
Synonyms	Lime stone, Calcite

<b>2. Composition /information on ingredients</b>			
Component	CAS	EINECS	% of composition
Calcium Carbonate	13397-26-7		98-99%

<b>3. Hazards Identification</b>	
Inhalation	Excessive exposure may cause symptoms of chronic lung disease.
Ingestion	The product is of low solubility in body fluids and it is likely to be of low toxicity
Eyes	May cause physical irritation and inflammation.
Skin	The material is not a primary irritant, but as with any abrasive powder it may give rise to minor irritation.

<b>4. First Aid Measures</b>	
Inhalation	Remove patient to fresh air, loosen tight clothing and seek medical attention.
Ingestion	Do not induce vomiting, seek medical advice.
Eyes	Wash immediately with copious amounts of water.
Skin	Wash affected areas with water.

<b>5. Fire Fighting Hazards</b>	
Extinguishing Media	Those suitable for surrounding fire conditions
Special Exposure Hazard	None
Personal Protective Equipment	None other than required for surrounding fire conditions.

<b>6. Accidental Release Measures</b>	
Leaks and Spills	Use suitable vacuum equipment where reasonably practicable, otherwise damp down and scoop into a receptacle.
Personal protective equipment	Respiratory protective equipment.



<b>7. Handling &amp; Storage</b>	
Handling	Do not eat, drink or smoke in areas where the material is used. Wash thoroughly after handling the material.
Storage	No special storage precautions required.

<b>8. Exposure Control/Personal Protection</b>	
Engineering controls	Adequate ventilation should be provided so that Occupational Exposure Limits are not exceeded. Local Exhaust Ventilation is normally recommended.
Personal Protective Equipment	Where LEV is not practicable and exposure is likely to be excessive, approved respiratory protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves and overalls are recommended for prolonged contact.

<b>9. Physical &amp; Chemical Properties</b>	
Appearance and Odour	Fine, white powder, odourless
Flash point (°C)	Not applicable
Flammability	Not applicable
Explosive properties	Non-explosive
Oxidising properties	None
Specific Gravity	2.72g/cm <sup>3</sup>
pH Value	9 (insoluble in water)
Melting point (°C)	-

<b>10. Stability &amp; Reactivity</b>	
Chemical stability	The material is stable
Conditions/ materials to avoid	None
Hazardous decomposition products	Contact with acids will release carbon dioxide and heating above 800 °C will release carbon dioxide.
Hazardous polymerization products	None

<b>11. Toxicological Information</b>	
Acute toxicology	None known
Health effects	Prolonged or repeated exposure above Occupational Exposure Standards may cause fibrosis of the lungs.

<b>12. Ecological Information</b>	
Ecotoxicity	Not known
Persistence	The material is stable and will persist in the environment.

<b>13. Disposal Considerations</b>	
Dispose in accordance with current waste disposal regulations (for UK – Control of Pollution {Special Waste} Regulations 1980). Landfill is the most appropriate method.	



14. Transport Information		
UN/SI No.		
UN Class		Not restricted
Packing group		Not restricted
Road	UK	Not restricted
	ADR	Not restricted
Sea	IMO	Not restricted
Air	ICAO	Not restricted

15. Regulatory Information			
EC Supply Labelling			
R Phases		Non Hazardous	
S Phases		None	
S Phases		Optional for dusty powders	
		S20/21	When using do not eat, drink or smoke.
		S38	In case of insufficient ventilation wear suitable respiratory equipment.
UK Occupational Exposures Limits (Refer to HSE Guidance note EH40)			
	Mg/m <sup>3</sup>	8 hr TWA	% in product
Dusts – Total Inhalable		10	-
Dusts – Total Respirable		5	-
<p>In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitute the user's assessment of workplace risk.</p>			

16. Other Information	
References	
COSHH ACOP	HSC approved Code of Practice for the Control of Substances Hazardous to Health Regulations 1994.
CHIP 96	Chemicals (Hazard Information and Packaging for Supply) Regulations 1996
CHIO SDS ACOPS	HSC Approved Code of Practice for Safety data Sheets in accordance with Regulation 6 of the CHIP regulations.
HSE EH40	HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with the COSHH regulations.