



CLAYMAN

Morells Barn • Park Lane • Lower Bognor Road • Lagness • Chichester • West Sussex • PO20 1LR
Telephone: +44 (0) 1243 265845 (2 lines + ansaphone) • Facsimile: +44 (0) 1243 267582

Email: info@claymansupplies.co.uk • www.claymansupplies.co.uk

PRODUCT INFORMATION

7214 – MOTORISED SLAB ROLLER



The Motorised slab roller is fully automatic , the operator simply places the clay on the slab roller adjusts to the required thickness closes the interlocked safety cage and then presses the cycle button . The slab roller will then make two passes over the clay and then come to a complete stop.

It is labour saving i.e. whilst the clay is being rolled it leaves you free to proceed with other duties around the class room or studio, extremely safe in operation , out standing results are produced from the combination of constant pressure at a set speed , ideal for the handicapped or physically impaired.

The slab roller uses the same excellent standard of engineering as our other slab rollers. The main roller is manufactured from corrosion resistant alloy and has infinite adjustment between approximately 2mm and 30mm via a centrally mounted threaded adjusting handle, thus eliminating the need for packing boards.



Technical Data

Drive: 0.37 Kw (0.5 Hp) worm reduction 1 phase or 3 phase
Speed control: Variable speed with full logic control
Safety: Fully enclosed and electrically interlocked safety cage
Power supply: 220/240 v50Hz/60Hz 380v 415 v
Slab size: 1020 mm x 470 mm wide
Dimensions : 1200 mm high x 915 mm wide x 1220 mm long
Weight: 90 Kilos

Please note slab size can only be given as a approximation due to the different natures of clay used.